2W Mini Pole Spotlight

Miniature LED fixtures for display cases, vitrines and retail cabinetry · 12 V DC low voltage system

Model	CHIA2411-2W
Rated power	2*1W
Input voltage	90-260V
Light source	COB
LED chip	Bridgelux
Colour temperature	3000k,4000k,6000k
CRI	>=80
Luminous flux	180 Lm
Beam angle	110
Housing material	Aviation aluminium
Housing finish	Customized
Rated life	20,000 h
Warranty	3 years

Technical files

Document	Format	Availability
Datasheet (this document)	PDF	Included
Photometric file (IES / LDT)	IES, LDT	On request
Dimension & cut-out drawing	DXF, PDF	On request
Installation instructions	PDF	On request
Test report (LM-80, flicker, CRI)	PDF	On request

Need this specified for a real cabinet?
Send the case photo, internal dimensions and what is displayed — we return a configuration with fixture count, beam angles, driver sizing and lead time. Samples: about 3 days. MOQ 1 pc. Warranty 3 years.
lightrixtech.com · info@lightrixtech.com · WhatsApp +86 159 0082 9072

Photometric files (IES / LDT), dimension and cut-out drawings (DXF), installation instructions and test reports are issued per configuration. Values above are nominal at 25 °C and refer to the standard configuration; confirm the exact variant with our engineering team before releasing for production.