# Mini Spotlight CHIB7520-3P-1W Precision Accent Lighting in Display Cases, Jewelry Showcases, Retail Shelving

Miniature LED fixtures for display cases, vitrines and retail cabinetry · 12 V DC low voltage system

| | |
|---|---|
| Model | CHIB7520-3P-1W |
| Rated power | 1 × 1W |
| Input voltage | DC 12V |
| LED chip | OSRAM SMD |
| Colour temperature | 3000K / 4000K / 6000K |
| CRI | Ra90 |
| Luminous flux | 150 Lm |
| Beam angle | 8° / 25° / 45° / 80° |
| Mounting | M8 Connector |
| Housing material | Aluminum |
| Housing finish | Black / Silver / White |
| Net weight | 20g |
| Gross weight | 25g |
| Carton Packaging | 60mm × 40mm × 20mm |
| Notes | Versatile for any display or accent lighting scenario |

### Technical files

| Document | Format | Availability |
|---|---|---|
| Datasheet (this document) | PDF | Included |
| Photometric file (IES / LDT) | IES, LDT | On request |
| Dimension & cut-out drawing | DXF, PDF | On request |
| Installation instructions | PDF | On request |
| Test report (LM-80, flicker, CRI) | PDF | On request |

**Need this specified for a real cabinet?**
Send the case photo, internal dimensions and what is displayed — we return a configuration with fixture count, beam angles, driver sizing and lead time. Samples: about 3 days. MOQ 1 pc. Warranty 3 years.
lightrixtech.com · info@lightrixtech.com · WhatsApp +86 159 0082 9072

Photometric files (IES / LDT), dimension and cut-out drawings (DXF), installation instructions and test reports are issued per configuration. Values above are nominal at 25 °C and refer to the standard configuration; confirm the exact variant with our engineering team before releasing for production.